



## WT 450

### TROLLEYS



Trolley used at the end of the line as a single tool for storing the finished doors and windows in the factory and transporting them to the worksite.



### Preparation for lifting

It allows it to be lifted easily by forklift as it is equipped with a fork housing. It also has hooks that ensure lifting by crane.



### Preparation for transport

Very easily and quickly, the pivoting wheels with brakes can be removed so that the carriage can rest on its own rubber feet to ensure safe truck transport.



### Surface in nonslip PVC

The working surfaces are covered with soft nonslip PVC that provides secure support when positioning the door.



### Pivoting wheels

Equipped with 4 pivoting wheels, 2 of which with brakes, that ensure a high degree of mobility and easy handling of the object. Locking the braking units allows their position to be fixed near different work areas.

**WT 450 / TROLLEYS**
**CHARACTERISTICS**

|                                                      |             |
|------------------------------------------------------|-------------|
| Lifting and suspension hooks                         | ●           |
| Modular structure base (mm)                          | 970 x 1.730 |
| Modular structure height (mm)                        | 1.805       |
| Removable wheels for trucking                        | ●           |
| Soft PVC contact surface                             | ●           |
| 4 swivel casters, 2 of which have locking stops (mm) | Ø = 125     |
| Load capacity (kg)                                   | 400         |
| Weight (kg)                                          | 77          |

Included ● Available ○